




DECLARATION OF PERFORMANCE
DoP-1187-130701

Comtrac
50/50 B20



Intended function(s): Reinforcement + Separation + Filtration

HUESKER Synthetic GmbH
Fabrikstraße 13–15
48712 Gescher, Deutschland
Tel. +49 (0) 25 42 / 701 - 0
Fax. +49 (0) 25 42 / 701 – 499
E-Mail: info@HUESKER.de
Factory A

System 2+

Notified body No. 0799 Kiwa MPA Bautest GmbH, Niederlassung TBU Greven performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.

Essential characteristics	Performance	Harmonised technical specification
Tensile strength T_{max} (EN ISO 10319)	MD 50 kN/m (- 0 kN/m) CMD 50 kN/m (- 0 kN/m)	EN13249:2000 + A1:2005 EN13250:2000 + A1:2005 EN13251:2000 + A1:2005 EN13253:2000 + A1:2005 EN13254:2000 + A1:2005 EN13255:2000 + A1:2005 EN13257:2000 + A1:2005 EN13265:2000 + A1:2005
Elongation ϵ_{max} (EN ISO 10319)	MD 10,5 % (\pm 1,5 %) CMD 10,5% (\pm 1,5%)	
Resistance to static puncture F_P (EN ISO 12236)	3,5 kN (- 0,5 kN)	
Dynamic perforation resistance D_C (EN ISO 13433)	9 mm (+ 3 mm)	
Characteristic opening size (EN ISO 12956)	130 μ m (\pm 50 μ m)	
Water permeability (EN ISO 11058)	120 l/m ² s (- 40 l/m ² s)	
Durability (Annex B)	To be covered within two weeks after installation. Predicted to be durable for a minimum of 25 years in natural soils with 4 < pH < 9 and a soil temperatures < 25°C.	

Gescher 01.07.2013

Helko Pintz
(Manager Quality Assurance)