

HUESKER Synthetic GmbH

Fabrikstraße 13-15 · D-48712 Gescher

Postfach 1262 · D-48705 Gescher

Telefon +49 (0) 25 42/ 7 01-0

Telefax +49 (0) 25 42/ 7 01-499

 Internet: <http://www.huesker.com>

 E-mail: info@huesker.de


SoilTain[®] PP 105/105 DW

DATA SHEET

**Woven PP - Fabric
for dewatering applications**



S
E
P
A
R
A
T
I
O
N

PRODUCT DATA:

| | |
|---|-----------------------------|
| Raw Material | PP |
| Weight <i>EN ISO 9864</i> | ~ 440 g/m ² |
| Ultimate tensile strength <i>EN ISO 10.319</i> | |
| longitudinal | ≥ 105 kN/m |
| transversal | ≥ 105 kN/m |
| Strain at nominal tensile strength <i>EN ISO 10.319</i> | |
| longitudinal | < 10 % |
| Transversal | < 10 % |
| Opening size <i>EN ISO 12956</i> | 240 μm |
| (Tolerance) | ± 40 μm) |
| Water permeability index normal to the plane | 20 x 10 ⁻³ m/s |
| (Tolerance <i>(EN ISO 11.058)</i>) | - 2 x 10 ⁻³ m/s) |
| Standard dimensions | |
| Width | 5.20 m |
| Length | 200.00 m |

No responsibility is accepted for any change in product properties due to environmental influences and / or improper application or handling. Rights are reserved to modify the product to effect improvements.